


1A Series

Sealed Miniature Toggle Switches



IP 67
ACCORDING TO
EN 60529:1991+A1:2001
IEC 60029:2001

UL
E 187490

RoHS
compliant



SPECIFICATIONS

CONTACT RATING: Dependent upon contact material See page 17.

MECHANICAL LIFE: 30,000 make-and-break cycles.

CONTACT RESISTANCE: 10 mΩ max. initial @ 2-4VDC

100mA for both silver and gold plated contacts.

INSULATION RESISTANCE: 1,000 MΩ min.

DIELECTRIC STRENGTH: 1,000 Vrms min. @sea level.

OPERATING TEMPERATURE: -30°C to 85°C.

MATERIALS

CASE & BUSHING: Glass filled nylon 6/6, flame retardant, heat stabilized (UL94v-0).

ACTUATOR: Brass, chrome plated with internal, O-ring seal standard.

SWITCH SUPPORT: Brass or steel, tin plated.















SWITCH SUPPORT RETAINER: Stainless steel.

CONTACT / TERMINALS: Copper alloy, with Silver or gold plated.
(See Page 17)

HOW TO ORDER

MODEL NO.	ACTUATOR	BUSHING	TERMINATIONS	TERMINAL PLATING	SEAL	RoHS SOLDERING
<div> <div></div> <div></div> <div></div> <div></div> </div> <p>Model NO.</p> <p>1AS1 SP On-None-On</p> <p>1AS2 SP On-None-Mom.</p> <p>1AS3 SP On-Off-On</p> <p>1AS4 SP Mom.-Off-Mom.</p> <p>1AS5 SP On-Off -Mom.</p> <p>1AD1 DP On-None-On</p> <p>1AD2 DP On-None-Mom.</p> <p>1AD3 DP On-Off-On</p> <p>1AD4 DP Mom.-Off-Mom.</p> <p>1AD5 DP On-Off-Mom.</p> <p>1AD6 DP On-On-On</p> <p>1AD7 DP Mom.-On-Mom.</p> <p>1AD8 DP On-On-Mom.</p> <p>1A31 3P On-None-On</p> <p>1A32 3P On-None-Mom.</p> <p>1A33 3P On-Off-On</p> <p>1A34 3P Mom.-Off-Mom.</p> <p>1A35 3P On-Off-Mom.</p>	<div> <div></div> <div></div> </div> <p>Actuator</p> <p>T1 12.70 high</p> <p>T2 7.62 high</p> <p>TA Plastic, black 12.70 high</p> <p>TB Plastic, black 7.62 high</p> <p>TC Plastic, silver 12.70 high</p>	<div> <div></div> <div></div> <div></div> </div> <p>Bushing</p> <p>B1 8.89 high</p> <p>B4 6.10 high</p>	<div> <div></div> <div></div> <div></div> </div> <p>Terminations</p> <p>M1 Solder Lug</p> <p>M2 PC thru-hole</p> <p>M51 18.70 high, wire wrap</p> <p>M52 24.20 high, wire wrap</p> <p>M53 10.55 high, wire wrap</p> <p>M54 26.97 high, wire wrap</p> <p>M6 Right angle, PC thru-hole</p> <p>M6N Right angle, snap-in, PC thru-hole</p> <p>M7 Vertical right angle, PC thru-hole</p> <p>VS2 11.68 high, V-bracket</p> <p>V2N 11.68 high, snap-in V-bracket</p> <p>VS3 16.00 high, V-bracket</p>	<div> <div></div> </div> <p>Terminal plating</p> <p>Q Gold flash over silver</p> <p>R Gold</p> <p>G Gold, pure-tin</p> <p>S Gold flash over silver, pure-tin</p> <p>C Gold over silver</p> <p>K Gold over silver, pure-tin</p>	<div> <div></div> </div> <p>Seal</p> <p>E EPOXY (std)</p>	<div> <div></div> </div> <p>RoHS soldering</p> <p>□ RoHS Compliant</p> <p>S RoHS & Lead Free</p>


SWITCH FUNCTION

NO. POLES	UL/CSA MODEL NO.	MODEL NO.	SWITCH FUNCTION			CONNECTED TERMINALS / SCHEMATIC			
			POS.1	POS.2	POS.3	POS.1	POS.2	POS.3	
									
SP	Q11A11	1AS1	ON	NONE	ON		N/A		
	Q11A12	1AS2	ON	NONE	MOM		OPEN		
	Q11A13	1AS3	ON	OFF	ON				
	Q11A14	1AS4	MOM	OFF	MOM				
	Q11A15	1AS5	ON	OFF	MOM				
DP	Q11A21	1AD1	ON	NONE	ON		N/A		
	Q11A22	1AD2	ON	NONE	MOM		OPEN		
	Q11A23	1AD3	ON	OFF	ON				
	Q11A24	1AD4	MOM	OFF	MOM				
	Q11A25	1AD5	ON	OFF	MOM				
		Q11A26	1AD6	ON	ON	ON	2-3,5-6	2-3,5-4	2-1,5-4
		Q11A27	1AD7	MOM	ON	MOM			
	Q11A28	1AD8	ON	ON	MOM				
3P	Q11A31	1A31	ON	NONE	ON		N/A		
	Q11A32	1A32	ON	NONE	MOM		OPEN		
	Q11A33	1A33	ON	OFF	ON				
	Q11A34	1A34	MOM	OFF	MOM				
	Q11A35	1A35	ON	OFF	MOM				

MOM=MOMENTARY

▲ Please check the availability in advance before order

POLE OPTIONS






SPDT

Part No. Shown : 1AS1T1B1M1QE

1A Series




Sealed Miniature Toggle Switches

1A
Toggle Switches



DPDT

Part No. Shown : 1AD1T1B4M2QE




3PDT

Part No. Shown : 1A31T1B4M2QE

ACTUATOR OPTIONS


Actuator shown with standard B4 Bushing,
Subtract .085 (2.15) for B1 bushing.

T1




Standard with
M1,M2 terminations.

T2




Standard with
M6,M7,VS2-3 terminations.

TA




TB



PLASTIC ACTUATOR
(TC,Silver)


BUSHING OPTIONS

B1



Std for M1


B4




Std for M2, M6, M7, VS termination

TERMINATION OPTIONS


M1 Solder lug




M2 PC Thru-hole



M3 Quick connect



M5 Wire Wrap



OTHER TERMINATION OPTIONS

M6 Right angle P.C. Mount



M7 Vertical right angle P.C. Mount

VS2 Vertical bracket P.C. Mount

VS3 Vertical bracket P.C. Mount


OPTION CODE	DIM. 'A'
M51	.736 (18.70)
M52	.953 (24.20)
M53	.415 (10.55)
M54	1.062 (26.97)

M6



SECTION A-A
TERM. NOS. FOR
REFERENCE ONLY



P.C. MOUNTING



SPDT


Part No. Shown : 1AS1T2B4M6QE

M6



SECTION A-A
TERM. NOS. FOR
REFERENCE ONLY



P.C. MOUNTING



DPDT


Part No. Shown : 1AD1T2B4M6QE

M7



SECTION A-A
TERM. NOS. FOR
REFERENCE ONLY

P.C. MOUNTING




SPDT

Part No. Shown : 1AS1T2B4M7RE


1A Series

Sealed Miniature Toggle Switches

M7




P.C. MOUNTING




DPDT

Part No. Shown : 1AD1T2B4M7RE

M7




P.C. MOUNTING




3PDT

Part No. Shown : 1A31T2B4M7QE

VS2 - VS3




P.C. MOUNTING




SPDT

Part No. Shown : 1AS1T2B4VS2QE

VS2 - VS3





P.C. MOUNTING




DPDT

Part No. Shown : 1AD1T2B4VS2QE

VS2 - VS3



OPTION CODE	DIM. 'A'
VS2	.460 11.68
VS3	.630 16.00




3PDT


Part No. Shown : 1A31T2B4VS2QE

SNAP-IN TERMINATION OPTIONS

M6N




V2N




HARDWARE

1/4 NUT




MNU-1M01A

LOCKING RING



MNU-1M02

LOCK WASHER



MNU-1M03

CONTACT MATERIAL OPTIONS

	CONTACT PLATING	TERMINAL PLATING	RATINGS
Q	Silver	Q = Gold flash over silver	5 Amps with resistant load @ 120VAC or 28VDC 2 Amps with resistant load @ 250VAC
S		S = Gold flash over silver,pure - tin	
C	Gold over Silver	C = Gold over silver	
K		K = Gold over silver,pure - tin	
R	Gold	R = Gold	0.4 Volt - Amps (VA) max. @ 20V max. (AC or DC)
G		G = Gold,pure - tin	

SOLDERING PROCESSES

MANUAL SOLDERING: Use soldering iron of 30 watts, controlled at 350°C
approximately 5 seconds while applying solder.

WAVE SOLDERING: Recommended Soldering Temperature: 260 ± 5°C

Duration of Solder Immersion: Max 5 sec. (PCB is 1.6mm in thickness)

1A Series

Sealed Toggle Switches

SPECIFICATIONS

CONTACT RATING: 0.4Volt-Amps(VA) max. @20V max(AC or DC)

MECHANICAL LIFE: 100,000 make-and-break cycles.

ELECTRICAL LIFE: 50,000 cycles.

CONTACT RESISTANCE: 10 mΩ max. initial @ 2-4VDC
100mA for both silver and gold plated contacts.

INSULATION RESISTANCE: 1,000 MΩ min.

DIELECTRIC STRENGTH: 1,000 V RMS@sea level.

OPERATING TEMPERATURE: -30°C to 85°C.

GENERAL SPECIFICATIONS

TORQUE: 0.8Nm max. applied to unt.

PANEL THICKNESS: 6mm max. ,2mm min.

MATERIALS

CASE & BUSHING: Glass filled nylon 6/6, flame retardant, heat stabilized (UL94v-0).

ACTUATOR: Brass, chrome plated with internal, O-ring seal standard.

SWITCH SUPPORT: Brass or steel, tin plated.









CONTACT / TERMINALS: Copper alloy, gold plated.

SEALIND: IP67.

IP 67
ACCORDING TO
EN 60529 1991+A1:2001
IEC 60529:2001




SWITCH FUNCTION

NO. POLES	MODEL NO.	SWITCH FUNCTION			CONNECTED TERMINALS / SCHEMATIC		
		POS.1	POS.2	POS.3	POS.1	POS.2	POS.3
							
SP	1AS1	ON	NONE	ON	<div>2-3</div> 	N/A	<div>2-1</div> 
	1AS2	ON	NONE	MOM			
	1AS3	ON	OFF	ON			
	1AS4	MOM	OFF	MOM			
	1AS5	ON	OFF	MOM			
	1AS9	ON	NONE	OFF	<div>2-3</div>	N/A	OPEN
	1ASD	MOM	NONE	OFF			

MOM=MOMENTARY


M1




Part No. Shown : 1AS1T8B22M1RPES

PANEL MOUNTING / HARDWARE

PANEL MOUNTING



NUT



SEALING BOOTS

