

印制电路板  
printed-circuit board



常态 FREE 1-1, 4-5  
按下 PUSH 2-3, 4-5  
电路图  
ircuit diagram

## FEATURES

- Light operating force.
- Long term low contact resistance.
- Momentary or latching operation.
- Short stroke 1.5mm to latch.
- Compact spacing on PCB of 14.0mm.

## SPECIFICATIONS


### 1.ELECTRICAL

● Contact rating	0.1A, 30VDC
● Contact resistance	50mWMax.
● Insulation resistance	100MWMin. at 250VDC
● Dielectric strength	250VAC Min. for 60 sec.

### 2.MECHANICAL AND ENVIRONMENTAL

● Temperature rating	Operating: -15℃ to +55℃ Storage: -25℃ to +65℃
● Operation force	200±80gf
● Stroke	Lock Stroke: 1.5±0.2mm Full Stroke: 2.5±0.2mm
● Operating life	full load: 50000cycles no load: 50000cycles
● Contact form	DPDT

PAPT NO	XKB1A01-X-X
OPERATION	W:NO LOCK Z:LOCK
COLOR	R:RED BL:BLUE

							DSND		DATE		SCALE: N/A	MODEL TYPE: PUSH SWITCH				
					ANGLAR	±5°	DWN		DATE		VIEW: 	PART NO.: XKB10A01				
△X					L ≤ 4	±0.2	CHKD		DATE		UNIT: mm	DWG NO.: XKB10A01—X—X				
△X					4<L ≤ 16	±0.3										
△X					16<L ≤ 63	±0.4										
MARK	DESCRIPTION			DATE	REVISED	APPROVED	L > 63	±0.5	APPD		DATE		SIZE: A4			
REVISIONS							UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED				WEIGHT	SHEET	REVISION	
													1.0g	1/1	A0	
www.xk-dg.cn   www.helloxkb.com   www.helloxkb.cn																