



NOTE:
Rating: DC 12V 50mA
Operating Force: 200±100gf
Lifetime: 100,000 Cycles

PAPT NO	L
SS-3235S-L1	2.0
SS-3235S-L2	3.0
SS-3235S-L3	4.0

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	6	Brass (0.30t)	ag Plated	—
④	Contact spring	—	1	Beryllium copper	—	—
③	Base	—	1	LCP	—	—
②	Cover	—	1	SUS	Tin plated	—
①	Keystake	—	1	PA46	—	—

					DSND		DATE		SCALE: N/A	MODEL TYPE: SLIDE SWITCH		
					DWN		DATE		VIEW:	PART NO.:		
					CHKD		DATE		UNIT: mm	DWG NO.: SS-3235S-X		
					APPD		DATE		SIZE: A4			
					XKB INDUSTRIAL PRECISION CO.,LIMITED					WEIGHT	SHEET	REVISION
										1.0g	1/1	A0

ΔX					ANGLAR	±5°
ΔX					L ≤ 4	±0.2
ΔX					4 < L ≤ 16	±0.3
ΔX					16 < L ≤ 63	±0.4
MARK					L > 63	±0.5

REVISIONS	UNSPECIFIED TOLERANCES
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn	