


NOTE:
Rating: DC 12V 50mA
Operating
Force:200±100gf
Lifetime:100,000
Cycles

SWITCH CONNECTOR

PAPT NO	L
SS-3380S-L1	2.0
SS-3380S-L2	3.0
SS-3380S-L3	4.0

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	6	Brass (0.30t)	ag Plated	—
④	Contact spring	—	1	Beryllium copper	—	—
③	Base	—	1	LCP	—	—
②	Cover	—	1	SUS	Tin plated	—
①	Keystake	—	1	PA46	—	—

							DSND		DATE		SCALE: N/A	MODEL TYPE: SLIDE SWITCH		
					ANGLAR	±5°	DWN		DATE		VIEW: 	PART NO.:		
△ X					L ≤ 4	±0.2	CHKD		DATE		UNIT: mm	DWG NO.:		
△ X					4<L ≤ 16	±0.3						SS-3380S-X		
△ X					16<L ≤ 63	±0.4	APPD		DATE		SIZE: A4			
MARK	DESCRIPTION			DATE	REVISED	APPROVED								
REVISIONS						UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED				WEIGHT	SHEET	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn												1.0g	1/1	A0