


SPECIFICATION
1.Rating:DC 12V 50mA Max
2.Contact resistance: 500mΩ MAX
3.Insulation resistance: 100MΩ Min
4.Dielectric strength: 250VAC/min
5.TRAVEL: CENTER 0.15±0.10mm
(4-DIRECTION)0.25±0.15mm

PAPT NO	TM-4175-X-X		
Operating force	A	4 Direction	180±50gf
	B	Center	250±50gf
Height			
	B	4 Direction	240±50gf
		Center	360±50gf
Height		H:A:5 B:6	

							DSND		DATE		SCALE: N/A	MODEL TYPE: MULTIFUNCTIONAL SWITCHS			
					ANGLAR	±5°	DWN		DATE		VIEW: 	PART NO.:			
△X					L≤4	±0.2	CHKD		DATE		UNIT: mm	DWG NO.:			
△X					4<L≤16	±0.3						TM-4175-X-X			
△X					16<L≤63	±0.4									
MARK	DESCRIPTION			DATE	REVISED	APPROVED	L>63	±0.5	APPD		DATE		SIZE: A4		
REVISIONS							UNSPECIFIED TOLERANCES		XKB INDUSTRIAL PRECISION CO.,LIMITED				WEIGHT	SHEET	REVISION
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn													1.0g	1/1	A0