

PC MOUNTING

Model No.	POS.1	POS.2	POS.3
2US4	MOM	OFF	MOM
Term. Comm.	5-6	OPEN	5-4
SCHEMATIC			

SWITCH FUNCTION

SPECIFICATIONS

MECHANICAL LIFE: 40,000 make-and-break cycles.

CONTACT RATING: 0.4 VA max. @ 20 V AC or DC max.

CONTACT RESISTANCE: Below 100 mΩ typ. initial @ 2-4 V DC, 100 mA.

INSULATION RESISTANCE: 500 MΩ min.

DIELECTRIC STRENGTH: 500 Vrms min. @ sea level.

OPERATING TEMPERATURE: - 30°C to 85°C

MATERIALS

HOUSING AND BASE: Glass filled nylon 6/6 or 4/6 , flame retardant,heat stabilized(UL94V-0)

ACTUATOR: Glass filled nylon 6/6 , flame retardant, heat stabilized(UL94V-0), with standard internal o-ring seal.

SWITCH SUPPORT: Steel,with Sn plated. (A)

CONTACT: Phosphor bronze, with gold plate over nickel plate.

TERMINALS: C2680, with gold plate over nickel plate.

TERMINAL SEAL: Epoxy.All terminals insert molded.


NOTE: Specifications and materials listed above are for switches with standard options.

For information on specific and custom switches,consult Customer Service Center.

RoHS & Lead Free



德利威電子股份有限公司
DAILYWELL ELECTRONICS CO.,LTD.

	符號	原尺寸	修改後尺寸	變更日期	SCALE (比例)： 3：2	TITLE 圖 名	Sealed Ultraminiature Toggle Switches			SIZE 圖紙	A4
1	Ⓐ	套片電鍍材質由Ni改為Sn;依N1119修訂夾片材質		JAN-11-2018		DWG NO. 圖 號	2US4T1A1M7RES			UNIT 單位	inch mm
2	Ⓑ					REV. 版 本	B	DATE 日期	JAN - 15 - 2014	SHEET 張數	1 of 1
3	Ⓒ					CHECKED BY 審 核				DRAWN BY 製 圖	IRENE
4	Ⓓ										
5	Ⓔ										
					TOLERANCE (公差)： 0.00 mm ± 0.25mm 0.0 mm ± 0.40mm ANGULAR：± 5° FILE NAME：2USP0074						